





### ◆ CONSTRUCTION

PARTS	MATERIAL	REMARK
BELLOWS	SUS 304	SUS 316 (OPTION)
WIRE BRAIDS	SUS 304	
SEAL RING	SUS 304	SUS 316
FLANGE	CARBON STEEL	SUS 304 / 316

\* Flange with ANSI, JIS, DIN, B.S. Stanard.

### SPECIFICATION

Nominal Bore		Total Length		Bellows		Offset Movement		Working Pressure
				O.D.	T			
mm	Inch	mm	inch	mm	mm	mm	mm	kg/cm <sup>2</sup>
15	1/2	300	12	25.0	0.3	56	36	20
20	3/4	300	12	30.5	0.3	56	36	20
25	1	300	12	38.0	0.3	49	33	20
32	1-1/4	300	12	46.0	0.3	46	27	20
40	1-1/2	300	12	56.0	0.4	42	20	20
50	2	300	12	73.6	0.4	33	18	20
65	2-1/2	300	12	88.0	0.4	31	16	16
80	3	300	12	102.0	0.4	24	14	16
100	4	300	12	128.0	0.4	22	12	13
125	5	300	12	155.0	0.5	24	16	10
150	6	300	12	185.0	0.5	22	14	10
200	8	300	12	235.0	0.6	20	8	10
250	10	350	14	286.0	0.6	17	8	10
300	12	350	14	340.0	0.7	15	7	10

⚙ Higher pressure rating and movement are available upon request.